

Date 14.06.2001

BBUK Eng Drg No. BG0100

Rev. 02

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: "UV resistant" Glue
Product code: Glue 146

Date: 2001-06-14
Replace:

Company: Brandenburg UK Ltd
24 navigation Drive,
Hurst Business Park,
Brierley Hill,
West Midlands.
DY5 1UT. UK.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical description: Hot Melt Adhesive

3. HAZARDS IDENTIFICATION

No European Danger category (67/548/EEC and amendments).

Eye	As supplied: no hazard. As used: severe thermal hazard
Skin contact	As supplied: no hazard. As used: severe thermal hazard
Inhalation	Vapours and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.
Ingestion	Low order of toxicity.

4. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. Get medical attention if irritation persists.
Skin contact:	If hot: flush with cool water. Treat as wax or resin burn. Do not attempt to remove solidified adhesive. Get medical attention immediately. As supplied: non-hazardous.
Eye contact:	If hot: flush with cool water. Treat as wax or resin burn. Do not attempt to remove solidified adhesive. Get medical attention immediately. As supplied: remove as foreign body.
Ingestion	None required.

5. FIRE FIGHTING MEASURES

Autoflammability	Not applicable.
Flash point	>250°C
Extinguishing media	CO ₂ ; Dry chemical.
Fire fighting procedures	No special procedures are required.
Fire & Explosion hazards	Not applicable.
Hazardous combustion products	Carbon monoxide, carbon dioxide, unknown hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Spill or leakage:	Allow to cool and solidify. Scrape up and collect in suitable containers for disposal.
-------------------	--

7. HANDLING AND STORAGE

Storage temperature	Ambient.
Special sensitivity	No special sensitivity.
Handling/storage	Store in a cool, dry area. Precaution: this product should only be heated to recommended temperatures. The hazards of pyrolysis products are unknown.
Ventilation requirements	Local exhaust over glue chamber.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Ventilation:	Local ventilation over glue chamber.
Respiratory protection:	None required if good ventilation is maintained.
Eye protection:	Safety glasses, goggles or face shield to protect against splashing.
Hand protection:	Thermally resistant gloves should be worn.
Clothing requirements	Uniforms, coveralls, or a lab coat should be worn.

9. PHYSICAL AND CHEMICAL PROPERTIES

Pure substance or prep	Preparation
Physical form	Solid
Appearance/odour	Amber, no odour
pH as is	Not applicable
Boiling point	>250°C
Melting point	90 - 100°C
Solubility in water	Insoluble
Relative density	1.000

Volatiles None
Volatile organic compounds <1 g/l (180°C)

10. STABILITY AND REACTIVITY

Stability: Stable

11. TOXICOLOGICAL INFORMATION

Although this product has not been tested for Effects of chronic effects Exposure it is judged as having a low order of toxicity based on component information. Use of good industrial hygiene practices is recommended.

12. ECOLOGICAL INFORMATION

Effect on environment Unknown
Mobility Unknown
Persistence / degradability Unknown
Potential to bioaccumulate No
Ecotoxicity Unknown
Aquatic toxicity None established

13. DISPOSAL CONSIDERATION

Waste disposal methods Waste disposal should be in accordance with existing Community, National and local regulations.
Empty container warnings Not needed

14. TRANSPORT INFORMATION

ADR/RID Not applicable
CEPIC trencard number Not applicable
IMDG classification Not applicable
IATA classification Not applicable

15. REGULATORY INFORMATION

Directives 88/379/EEC have been considered when compiling this MSDS; the information is provided for health and safety assessment by an industrial user. Reference should be made to any relevant local or national health, safety, and environmental legislation. This information does not constitute indication of suitability for specific uses.

16. OTHER INFORMATION

FDA-status

complies with the composition requirements of "Food Packaging Adhesives" – 21CFR 175.105.